


# 24 Fiber Infinicor 600 Micro Distribution, Plenum

**Part Number  
M50MD24C6NPO**



The Light Connection's 24 fiber Micro Distribution Cable is composed of two sub units, an optional central member, an aramid ripcord, and a PVC outer jacket. Each sub-unit consists of 12 colored glass fibers surrounded by aramid yarn with a PVC jacket 2.95mm in diameter. All component materials meet the EU RoHS and REACH Directive standards. Sub-units can be color-coded or sequentially numbered.

TLC Micro Distribution Cable is available in 12 TIA standard colors or special-order colors. UL Listed OFNP cables are available, and unlisted, unrated cable can be supplied to accommodate special needs. Standard surface print denotes construction, NEC rating and fiber type, and includes footage markers. Custom print can also be accommodated.



## Product Specifications

Storage Temp. (C°)  
-40 / +85

Operating Temp. (C°)  
-20 / +85

## Jacket Characteristics

TLC Part Number	Jacket Material	Fiber Count	Nominal Dimension	Weight* lbs. / Km	Pull Load* (N) Install / Operate	Bend Radius* (cm) Install / Operate
M50MD24C3NPO	PVC Orange	24	10 mm	85	5328/4263	15/10

## Optical Characteristics

Fiber Type	Core Size	Attenuation (MAX)	Bandwidth (LED) 850 nm	Bandwidth (LED) 1300 nm	Link Lengths @ 850nm 1 GB/s
Infinicor 600	50/125	3.50 dB/km @ 850nm	510	500	600 mtr

For more information on the fiber characteristics, please consult with your TLC representative.  
You can also visit the TLC website at [www.thelightconnection.com](http://www.thelightconnection.com)



Address: 132 Base Road, Oriskany, NY 13424  
Phone: 315 736-7384  
Fax: 315 736-1927  
Email: [info@thelightconnection.com](mailto:info@thelightconnection.com)  
On the web: [www.thelightconnection.com](http://www.thelightconnection.com)

REV-3.0 Date- 11/17/09

Supersedes REV- 2.0 Date- 10/06/09