


# 2-6 Fiber Infinicor 300 Indoor/Outdoor, Riser

INDOOR/OUTDOOR



The Light Connections Indoor/Outdoor Cable is composed of 2 to 6 colored tight buffers, water blocking aramid yarn, and a PVC outer jacket. All component materials meet the EU RoHS and REACH Directive standards.

TLC Indoor/Outdoor Cable is available in 12 TIA standard colors or special order colors. UL Listed OFNR cables are available, and unlisted, unrated cables can be supplied to accommodate special needs. Standard surface print denotes construction, NEC rating, and fiber type, and includes footage markers. Custom print can also be accommodated.



## Product Specifications

Storage Temp. (C°)  
-40 / +70

Operating Temp. (C°)  
-20 / +70

## Jacket Characteristics

TLC Part Number	Jacket Material	Fiber Count	Nominal Dimension	Weight lbs. / Km	Pull Load (N) Install / Operate	Bend Radius (cm) Install / Operate
M62IO02C3NRBL	PVC Black	2	4.4 mm	21	1998/1599	6.6/4.4
M62IO04C3NRBL	PVC Black	4	4.8 mm	27	1998/1599	7.2/4.8
M62IO06C3NRBL	PVC Black	6	5.3 mm	35	2664/2131	8.0/5.3

## Optical Characteristics

Fiber Type	Core Size	Attenuation (MAX)	Bandwidth (LED) 850 nm	Bandwidth (LED) 1300 nm	Link Lengths @ 850nm 1 GB/s
Infinicor 300	62.5/125	3.50 dB/km @ 850nm	200 MHz	500 MHz	300 mtr

For more information on the fiber characteristics, please consult with your TLC representative. You can also visit the TLC website at [www.thelightconnection.com](http://www.thelightconnection.com)



Address: 132 Base Road, Oriskany, NY 13424  
 Phone: 315 736-7384  
 Fax: 315 736-1927  
 Email: [info@thelightconnection.com](mailto:info@thelightconnection.com)  
 On the web: [www.thelightconnection.com](http://www.thelightconnection.com)

REV-3.0 Date- 12/15/09

Supersedes REV- 2.0 Date- 10/16/09

