



36 Fiber SMF28e+ Dry Loose Tube, Riser

**Part Number
S09DL36CNRBL**



The Light Connection's Multi-tube Dry loose Tube Cable is composed of 3 sub-units, water blocking yarn, an optional central strength member, an aramid ripcord, and a PVC outer jacket. Each sub-unit consists of 12 colored glass fibers and water swellable yarn with a PVC jacket 3mm in diameter. All component materials meet the EU RoHS and REACH Directive standards. Sub-units can be color-coded or sequentially numbered.

TLC Dry Loose Tube is available in 12 TIA standard colors or special order colors. UL Listed OFNR cables are available, and unlisted, unrated cables can be supplied to accommodate special needs. Standard surface print denotes construction, NEC rating and fiber type, and includes footage markers. Custom print can also be accommodated.



Product Specifications

Storage Temp. (C°)
-40 / +70

Operating Temp. (C°)
-20 / +70

Cable Characteristics

TLC Part Number	Jacket Material	Fiber Count	Nominal Dimension	Weight lbs. / Km	Pull Load (N) Install / Operate	Bend Radius (cm) Install / Operate
S09DL36CNRBL	PVC Black	36	10 mm	153	3996/ 3197	15 / 10

Optical Characteristics

Fiber Type	Core Size	Attenuation (MAX)	Link Lengths @ 1550nm 1 GB/s / 10 GB/s
SMF28e+	9/125	0.50 dB/km @ 1550nm	10,000 mtr / 5,000 mtr

For more information on the fiber characteristics, please consult with your TLC representative. You can also visit the TLC website at www.thelightconnection.com



Address: 132 Base Road, Oriskany, NY 13424
Phone: 315 736-7384
Fax: 315 736-1927
Email: info@thelightconnection.com
On the web: www.thelightconnection.com

REV-1.0 Date- 9/22/11

Supersedes REV- 0.0 Date- 7/21/09