


# 48 Fiber SMF28e+ Micro Distribution, Riser

**Part Number  
S09MD48CNR**



The Light Connection's 48 fiber Micro Distribution Cable is composed of four sub units, an optional central member, an aramid ripcord, and a PVC outer jacket. Each sub-unit consists of 12 colored glass fibers surrounded by aramid yarn with a PVC jacket 2.95mm in diameter. All component materials meet the EU RoHS and REACH Directive standards. Sub-units can be color-coded or sequentially numbered.

TLC Micro Distribution Cable is available in 12 TIA standard colors or special-order colors. UL Listed OFNR cables are available, and unlisted, unrated cable can be supplied to accommodate special needs. Standard surface print denotes construction, NEC rating and fiber type, and includes footage markers. Custom print can also be accommodated.



## Product Specifications

Storage Temp. (C°)  
-40 / +70

Operating Temp. (C°)  
-20 / +70

## Cable Characteristics

TLC Part Number	Jacket Material	Fiber Count	Nominal Dimension	Weight lbs. / Km	Pull Load (N) Install / Operate	Bend Radius (cm) Install / Operate
S09MD48CNR	PVC Yellow	48	10 mm	127	5328/4263	15/10

## Optical Characteristics

Fiber Type	Core Size	Attenuation (MAX)	Link Lengths @ 1550nm 1 GB/s / 10 GB/s
SMF28e+	9/125	0.80 dB/km @ 1550nm	5,000 mtr / 10,000 mtr

For more information on the fiber characteristics, please consult with your TLC representative. You can also visit the TLC website at [www.thelightconnection.com](http://www.thelightconnection.com)



Address: 132 Base Road, Oriskany, NY 13424  
Phone: 315 736-7384  
Fax: 315 736-1927  
Email: [info@thelightconnection.com](mailto:info@thelightconnection.com)  
On the web: [www.thelightconnection.com](http://www.thelightconnection.com)

REV-1.0 Date- 8/4/09

Supersedes REV- 0.0 Date- 7/21/09